



TAYLOR meta-tec® MS-PLUS WOOD FLOORING ADHESIVE

**NEW ADDITIONAL OUTSTANDING CHARACTERISTICS:
MOISTURE INHIBITOR/SOUND REDUCER**

In addition to being an excellent wood flooring adhesive, Taylor Meta-Tec® MS Plus is multi-functional as an effective concrete moisture inhibitor and as a sound reduction system.



CONCRETE MOISTURE INHIBITOR

For concrete slabs with elevated moisture levels up to **10lbs/1000ft²/24 hrs** (as measured by an anhydrous calcium chloride test kit according to ASTM F-1869 test method) or a Relative Humidity 85% or less (as tested per ASTM F-2170) use a pre-coat application of Taylor Meta-Tec® MS Plus according to the label instructions.

Using a **3/16" x 5/32" "V"** notch trowel, apply Taylor Meta-Tec® MS Plus over the entire installation area. Allow the moisture inhibitor/sound reduction film of adhesive to dry for a minimum of 4 hours prior to proceeding with the wood flooring installation.



SOUND REDUCTION SYSTEM

When properly applied as a pre-coat MS Plus will exceed IIC and STC Building Code requirements.

IIC = 66 ASTM E 492-04
IIC = 52 ASTM E 492-04

STC = 65 ASTM E90-04
STC = 51 ASTM E90-04

with ceiling
without ceiling

-Technical data available upon request.

The adhesive for the wood installation should be applied with the recommended trowel (see trowel sizes on bucket label) in a swirling motion so as to fill in the gaps present in the dried moisture inhibitor/sound reduction film of adhesive, and to leave new trowel ridges in which to set the wood. Complete the installation using the standard wood installation procedures described in the Taylor Meta-Tec® MS Plus brochure.



GREENGUARD® CERTIFIED

Taylor Meta-Tec® MS Plus, along with Taylor's other flooring adhesives, are the **FIRST** to acquire GREENGUARD® certification flooring adhesives available to the market, ensuring compliance with stringent **environmental standards and regulations**.

You may also visit us on the web at:
www.wftaylor.com or e-mail us at
info@wftaylor.com

COVERAGES

**RECOMMENDED
TROWEL SIZES:**

Moisture Inhibitor and
Sound Reducer Application

50-60
ft² per gal.



* Combined with wood installation, 25 - 30 ft² per gallon.

* The inhibitor and sound reduction coating is a 2 step process which requires a second application of MS+ only to adhere wood surfaces down.

For complete warranty information,
call Taylor Technical Services at
800-868-4583 ext. 221



TAYLOR
Innovative Science. Applied Technology.™