



# MANNINGTON® COMMERCIAL SHEET AT A GLANCE

**Dealer:**

To order loose samples of these products call; 1-800-241-2262, Then press 1, then press 2

**Loose Samples available as:**

Small: 2"x2" chips  
3"x5" sheet  
Full size: 9"x12" sheet  
12"x12" VCT  
Full planks of NaturesPath / NaturesPath Select  
Small: 2"x6" Natures Path Planks  
4"x4" Natures Path Tile

NEW

Product	Wearlayer Mil	Warranty	Seam Sealer	Construction	Adhesive	Comm. Traffic	Width
<b>Primus</b>	Quantum Guard™ HP Urethane <sup>3</sup> 20 mil	5 year	Heat weld or MLG-33	Roto Gravure Vinyl <sup>4</sup>	V-82 (Porous) V-95 (Non-porous) V-68 <sup>1</sup> w/ MGuard	Heavy	12 ft cuts only, 6 ft or 9 ft rolls only
<b>Realities</b>	Quantum Guard™ HP Urethane <sup>3</sup> 20 mil	5 year	Heat Weld or MLG-33	Roto Gravure Vinyl <sup>4</sup>	V-82 (Porous) V-95 (Non-porous) V-68 <sup>1</sup> w/ MGuard	Heavy	12 ft cuts only, 6 ft or 9 ft rolls only
<b>Relay RE<sup>2</sup></b>	Quantum Guard™ HP Urethane <sup>3</sup> 30 mil	5 year	Heat weld or MLG-33	Inlaid/Recycled content	V-82 (Porous) V-95 (Non-porous) V-68 <sup>1</sup> w/ MGuard	Heavy	6 ft
<b>Magna Multiflec</b>	Quantum Guard™ 55 mil	5 year	Heat weld or MCS-42 w/ VST-96 Applicator	Inlaid/Felt	V-81	Heavy	6 ft
<b>Custom Spec II</b>	JT-88 PVC 20 mil	10 year	MCS-42 w/ VST-96 Applicator	Roto Gravure/Felt	V-81	Light/Medium	12 ft
<b>Insight</b>	JT-88 PVC 20 mil	10 year	MCS-42 w/ VST-96 Applicator	Roto Gravure/Felt	V-81	Light/Medium	12 ft
<b>Assurance II</b>	Quantum Guard™ HP Urethane <sup>3</sup> 80 mil	5 year	Heat weld or MLG-33	Inlaid/Homogeneous Slip Resistant	V-82 (Porous) V-95 (Non-porous) V-68 <sup>1</sup> w/ MGuard	Heavy	6 ft
<b>Bio Spec</b>	Quantum Guard™ 80 mil	5 year	Heat weld or MCS-42	Inlaid/Homogeneous	V-82 (Porous) V-95 (Non-porous) V-68 <sup>1</sup> w/ MGuard	Heavy	6 ft
<b>Fine Fields</b>	Quantum Guard™ 66 mil	5 year	Heat weld or MCS-42 w/ VST-96 Applicator	Inlaid/Felt	V-81	Heavy	6 ft
<b>Lifelines II</b>	Quantum Guard™ HP Urethane <sup>3</sup> 80 mil	5 year	Heat weld or MCS-42	Inlaid/Homogeneous	V-82 (Porous) V-95 (Non-porous) V-68 <sup>1</sup> w/ MGuard	Heavy	6 ft

<sup>1</sup> Mannington V-68 w/ MGuard can be used over concrete slabs with up to 8 lbs of MVE (Moisture Vapor Emissions) per ASTM F1869 or up to 80% RH (Relative Humidity) per ASTM Test Method F2170 without any further moisture vapor remediation.

<sup>2</sup> Relay RE contains 35% recycled content (20% post consumer, 15% pre consumer).

<sup>3</sup> Quantum Guard™ HP is Manningtons Patented high performance urethane wearlayer with an aluminum oxide topcoat cured by a UV process

<sup>4</sup>Primus and Realities are not recommended over wood substrates



November 2008

# MANNINGTON® VCT AT A GLANCE

Product	Visual	Recycled Content	Selling Points	Commercial Traffic	Adhesive	Warranty
Prime Essentials	Directional	NO	Valu-Priced	Heavy	V-11 w/ MGuard <sup>1</sup>	5 year
Essentials	Directional	NO	Valu-Priced	Heavy	V-11 w/ MGuard <sup>1</sup>	5 year
Designer Essentials	Direct/High Fashion	NO	Valu-Priced/Monolithic Visual	Heavy	V-11 w/ MGuard <sup>1</sup>	5 year
Inspirations	Premium/Directional	NO	Multi Colored	Heavy	V-11 w/ MGuard <sup>1</sup>	5 year
Solid Point	Premium/Non-direct	YES	Virtual Solid/Finely Textured	Heavy	V-11 w/ MGuard <sup>1</sup>	5 year
Color Point	Premium/Non-direct	YES	Confetti Pattern/Vibrant Color	Heavy	V-11 w/ MGuard <sup>1</sup>	5 year
Brushwork	Premium/Non-direct	YES	Artistic Brushstroke Design	Heavy	V-11 w/ MGuard <sup>1</sup>	5 year
Safewalks Slip Resistant	Premium/Non-direct	NO	Slip Resistant/Granite Visual	Heavy	V-11 w/ MGuard <sup>1</sup>	5 year

<sup>1</sup> Mannington V-11 w/ MGuard can be used over concrete slabs with up to 8 lbs of MVE (Moisture Vapor Emissions) per ASTM F1869 or up to 85% RH (Relative Humidity) per ASTM Test Method F2170 without any further moisture vapor remediation

**Dealer:**

To order loose samples of these products call; 1-800-241-2262, Then press 1, then press 2

**Loose Samples available as:**

- Small: 2"x2" chips
- 3"x5" sheet
- Full size: 9"x12" sheet
- 12"x12" VCT

Full planks of NaturesPath / NaturesPath Select

- Small: 2"x6" Natures Path Planks
- 4"x4" Natures Path Tile

# MANNINGTON® COMMERCIAL LUXURY VINYL AT A GLANCE

Product	Wearlayer Mil	Warranty	Construction	Available Sizes	Adhesive
<b>NEW</b> Assurance Squared	Quantum Guard™ HP Urethane <sup>2</sup> 20 mil	10 year	Vinyl Tile	18" x 18" Slip Resistant	V-82 (Porous) V-95 (Non-porous) V-68 <sup>1</sup> w/ MGuard
Natures Path	Quantum Guard™ HP Urethane <sup>2</sup> 20 mil	10 year	Vinyl Plank	3" x 36" 4" x 36" 6" x 36"	V-82 (Porous) V-95 (Non-porous) V-68 <sup>1</sup> w/ MGuard
Natures Path	Quantum Guard™ HP Urethane <sup>2</sup> 20 mil	10 year	Vinyl Tile	16" x 16"	V-82 (Porous) V-95 (Non-porous) V-68 <sup>1</sup> w/ MGuard
Natures Path Select	Quantum Guard™ HP Urethane <sup>2</sup> 20 mil	10 year	Vinyl Plank	3" x Random Lengths 5" x 48" 7" x 48"	V-82 (Porous) V-95 (Non-porous) V-68 <sup>1</sup> w/ MGuard
Natures Path Select	Quantum Guard™ HP Urethane <sup>2</sup> 20 mil	10 year	Vinyl Tile	18" x 18"	V-82 (Porous) V-95 (Non-porous) V-68 <sup>1</sup> w/ MGuard

<sup>1</sup> Mannington V-68 w/ MGuard can be used over concrete slabs with up to 8 lbs of MVE (Moisture Vapor Emissions) per ASTM F1869 or up to 80% RH (Relative Humidity) per ASTM Test Method F2170 without any further moisture vapor remediation

<sup>2</sup> Quantum Guard™ HP is Manningtons Patented high performance urethane wearlayer with an aluminum oxide topcoat cured by a UV process